

NOTES: UNLESS OTHERWISE SPECIFIED


1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER


- 2. MODIFICATIONS: N/A
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-2S* PLUG (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



| CONTACT | MIN. INSUL | | TYPICAL |
|---------|------------|-----------|--------------|
| SIZE | O.D. | | WIRE RANGE |
| 16 | 2.24 mm | 3.68 mm | 14 - 20 AWG |
| | (.088 in) | (.145 in) | (2.0-0.5mm²) |




| PART NUMBER CHART | | | |
|-------------------|-------------|--|--|
| COLOR | PART NUMBER | | |
| GREY | AT04-2P | | |
| BLACK | AT04-2P-BLK | | |
| BLUE | AT04-2P-BLU | | |
| BROWN | AT04-2P-BRN | | |
| GREEN | AT04-2P-GRN | | |
| RED | AT04-2P-RED | | |
| WHITE | AT04-2P-WHT | | |
| YELLOW | AT04-2P-YEL | | |
| ORANGE | AT04-2P-ORG | | |

| | | REVISIONS | | | |
|-----|--------|------------------------|---------|-------|-------|
| REV | ECO | DESCRIPTION | DATE | BY | APPR |
| A3 | - | RELEASE NEW DWG FORMAT | 26DEC13 | JARRY | |
| A4 | C0540S | UPDATE DIMENSIONS | 22JUN16 | JONY | TOMMY |
| A5 | - | ADD COLOR OPTION | 23NOV20 | LOUIE | TOMMY |

RECEPTACLE, 2 PIN, AT SERIES

AT04-2P-XXX



| | | | IONAL | COLORS | SHOWN IN | COLOR IS GREY PART NUMBER PECIAL ORDER | 1 | |
|---|----------------------------------|---|--|-----------|-------------------------------|--|-------------|-------|
| | SEE PART N | NUMBER CHART | | | REF:DT04-2P,DT04-2P-E004 | | | |
| | PART N | NUMBER | | | DESCRIPTION | | ITEM | |
| QUANTITY | | | MAT | ERI | ALS LIS | ST | | · |
| 1) All dimensions are 1) Tolerances are 1 PL DEC ±0.30 | as follows: Fractions ±1/64 | DRAWN: | LOUE | 23NOV20 | _ A | mphe | enc | |
| 2 PL DEC ±0.15 3 PL DEC ±0.08 Angles ±1° 3) Note reference = X | | ENGINEER: | ORION | 24NOV20 | | e Systems - www.amphe 44724 Morley Drive Clinton Township, MI 48 | | |
| MATERIAL SPECIFICATIONS: | | CUSTOMER: | IOMMY 25NOV20 | | RECEPTACLE, 2 PIN, AT SERIES, | | | RIES, |
| PROCESS SPECIFICATIONS: SPECIFICATIONS AS SPECIFICATIONS AS SHOWN HEREON AT THE AMPHENOL CO OF REPRODUCTION DIMENSIONS ARE SI | | NS AND PERFO ON ARE THE P OL CORPORAT | ORMANCE DATA ROPERTY OF ION. NO RIGHTS | B C- | MT04-21 | P-XXX | REVISION A5 | |
| NEXT ASS'Y | | | | TO NORMAL | SCALE: NONE | | | |